



**NEW**  
NOW WITH  
AUTO-EPAP



## Simplicity at your Fingertips

The Vivo 2 is a new generation ventilator designed for personalized and comfortable non-invasive respiratory support for non-dependent patients with chronic breathing insufficiency. The intuitive interface ensures ease of use. A comprehensive set of modes and extensive monitoring capabilities allow for great flexibility, making the ventilator a perfect choice for a variety of patients.

*See also separate product sheets for Vivo 1 and Vivo 3.*



### COMPACT

- One Platform – Three Models
- Lightweight and Compact
- Integrated Humidifier with heated wire circuit



### ADAPTABLE

- Wide range of Modes
- Adult and paediatric (>10kg)
- Intuitive Interface
- Extensive therapy data
- Suitable for use in hospital and home
- Closer monitoring with Breas accessory box



### CONNECTED

Making Connected Care more insightful

- EveryWare – Secure cloud-based remote monitoring\*
- PC Software – Desktop-based with Live Viewer



# Vivo 2 Technical Specifications

Settings / performance	
Ventilation Modes	S, ST, T, PSV, PCV+A, CPAP
Adult/Pediatric	>10kg
IPAP	4 - 30 cmH <sub>2</sub> O
EPAP	2 - 20 cm H <sub>2</sub> O
Breath Rate/Back-up Rate	0-40 bpm
Inspiratory Time	0.3 - 3 s
Rise Time	1 - 9
Inspiratory Trigger	1 - 9
Expiratory Trigger	1 - 9
Minimum Inspiratory Time	Off, 0.3 - 3 s
Maximum Inspiratory Time	Off 0.3 - 3 s
Target Volume	100 – 1500 ml
Target Volume	100 – 1500 ml
Auto-EPAP	On/Off, Pressure Limit: Max EPAP +2 cmH <sub>2</sub> O – 30 cmH <sub>2</sub> O, PS 2-28cm Min/Max EPAP: 2 - 20 cmH <sub>2</sub> O, EPAP Step: 0.5 - 2 cmH <sub>2</sub> O, Relax Time: 2-12mins/Off
Ramp (Up/Down)	Off 10-60mins
Humidifier Level	1-5
Heated Circuit	Off, 1-5
Patient Circuit	15mm, 22mm
O <sub>2</sub> Bleed in (Device)	0-30L/min
Monitoring	
Displayed data	Ppeak, EPAP, Leakage, MV, Vte % in TgV, Total Rate I:E, Spont Rate, % spont, Inspiratory time, Rise time, SpO <sub>2</sub> , Pulse, Rate
Power Supplies	
Mains supply	100 to 240 V AC
External DC	24 V
Alarms	
Alarms	High Pressure, Low Pressure, High Breath Rate, Low Breath Rate High MV, Low MV, Rebreathing Apnea, Disconnection, High SpO <sub>2</sub> , Low SpO <sub>2</sub> , High Pulse Rate, Low Pulse Rate, Power failure
Dimensions	
W x H x D	166 x 185 x 200 mm
Weight	1.6kg
Noise level (at 10 cmH <sub>2</sub> O constant pressure)	Less than 28 dB(A)
Connectivity and Software	
Built-in connectivity	USB
Compatible Software	PC Software and is prepared for EveryWare Remote Monitoring*
Plug-and-Play accessories	SpO <sub>2</sub> , Nurse Call, Remote Alarm, Accessories Box
Other	
Humidification	Integrable water chamber
Circuits	Cleanable & Disposable leakage circuits with/without heated wires
Confirm Stop	On, Off
Compliance Data (on Screen)	Min Daily Usage Off, 1-24hrs, Total Usage Hours, Total Days, Days with Usage, Average Usage, Days Compliant, AHI

\*Please contact Breas for availability

## Intended use:

Vivo 2 is intended to provide non-invasive ventilation for patients weighing over 10 kg (22 lbs) who require long-term support or mechanical ventilation for respiratory impairment, with or without obstructive sleep apnea. Vivo 2 is intended for spontaneously breathing patients.